

ZEKE-9-12V-SQR 12V LED Steplight



Description


The surface mounted ZEKE-9-Square features a slim-line, cast-aluminium body with dual cable glands for easy installation. The aluminium trim features a special chromate process before a polyester powder coated finish is applied, for extended wear in harsh external environments. With an IP65 rating, the ZEKE-9-Square features amazing downward illumination with minimal power consumption; A total of 9W of high intensity illumination. Particularly useful for outside entertaining areas, external pathways or any area in which recessed mounting is not an option. Now available in 12V DC models, to allow for outdoor applications such as planter boxes and front wall installations, where low voltage wiring has been used.



Specification Features

| Input Voltage: | 12V DC | |
|-----------------|---|--|
| Power (W): | 9W | |
| IP rating (IP): | IP65 | |
| Lumens (lm): | Warm White 3000K - 800lm White 5000K - 900lm | |
| LED type: | SMD | |
| CCT: | 3000К - 5000К | |
| CRI: | ≥85 | |
| Beam angle (°): | 120° | |
| Dimmable: | No | |
| Lifespan (hrs): | 50,000hrs | |
| Requires: | 12V DC Constant Voltage LED Driver | |

Diagrams / Additional



| Item No. | Variant | Colour |
|--------------------|---------|--------|
| ZEKE-9-12V-SQR-BLK | 19878 | 3000K |
| ZERE-9-12V-SQR-BLK | 19879 | 5000K |
| ZEKE-9-12V-SQR-DGR | 19874 | 3000K |
| ZERE-9-12V-SQR-DGR | 19875 | 5000K |
| ZEKE-9-12V-SQR-SLR | 19872 | 3000K |
| ZEKE-9-12V-SQK-SLK | 19873 | 5000K |
| | 19876 | 3000K |
| ZEKE-9-12V-SQR-WHT | 19877 | 5000K |

Domus Lighting 29-31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | Fax: (02) 9554 9433 | email: enquiries@domuslighting.com Specification subject to change without prior notice.