

PARK-120-WG

















LED Batten

Description

The PARK LED Batten series is a direct replacement to traditional T8 and T5 Wide Body Fluorescent battens. The PARK Series LED Batten also features a dual Wattage option. So, if the area is too bright, simply press the switch located on the LED Driver to reduce the light output by half. Pressed body is constructed from high-quality sheet metal, white powder coated with a choice of prismatic polycarbonate diffuser, or wire guard. Available in 600mm and 1200mm lengths, with TRIO, the added option of changing the colour temperature output of the LED batten with a dip switch located inside the fitting. Tricolour switchable LED Colour temperatures - Warm White 3000K, Neutral White 4000K, and White 5000K. Also available as part of a family of ON/OFF and DIM Sensor models as well as Emergency models. Suitable for domestic applications such as laundries, garage, storerooms. Also commercially for underground carparks.



Australian Designed for guick and easy installation Designed:

Input Voltage: 240V AC

130lm/W high output Dedicated LED Lumens:

Wattage: 15W/30W

Half power switch on the driver which decreases the lumen output by 50%

SMD 3000K, 4000K, 5000K (Switchable) CCT:

CRI ≥80 120° Beam angle (°): Dimmable:

Cover: Opal diffuser with even light output

Terminal: Large Terminal, PA16

Approval: Complies with AS2293.3-2005+AMD 1&2 Annex C / EMC compliant

20mm Knockouts for conduit or cable glands Feature:

Optional Internal Microwave Sensor options available – ON/OFF and Options:

DIM Sensor options. Setup Remote required for multiple setups to alter

default settings to achieve different modes (not supplied)

5 Year Warranty Warranty:




Internal ON/Off Sensor

Diagrams / Additional



1230mm



Variant			CCT
Non-Dim	ON/OFF Sensor*	DIM Sensor*	CCI
66063	66064	66065	TRIO
N/A	66090	66091	N/A
	66063	Non-Dim ON/OFF Sensor* 66063 66064	Non-Dim ON/OFF Sensor* DIM Sensor* 66063 66064 66065

*Remote Control Required

Dimmable Sensor