

## PLEX-ULTRA IP67


















# (Designed for long run lengths)



#### Description

The PLEX-ULTRA series is a specially designed LED Strip that reduces heat and resistance, allowing for longer runs than other LED Strip designs, still incorporating the latest in LED COB chip technology, with true dotless appearance utilising 560 LEDs per metre. Operating on 24V DC allows for less resistive heat and longer run lengths. Choose from IP54 Indoor Strip including wet areas, or for waterproof installations, the IP67 Strip with silicon coating. Longer areas of weldless joints provide a more reliable solution avoiding breaks in continuity. Available in 10W per metre, which provides a bright and desirable light output for your desired area.

High CRI90 chips provide excellent colour rendering while providing a smooth and seamless linear lighting for a clean and minimalistic look. The PLEX-ULTRA series come with a choice of single colour 3000K Warm White, 4000K Neutral White and 5000K White for your residential or commercial linear lighting project applications. A comprehensive range of optional accessories including fast fix connectors, and L-joint connectors are available for complex installations. Ideal for kitchens, bathrooms, laundry, bars, restaurants, and all indoor highlighting applications.

#### Specification Features

CCT: 3000K, 4000K & 5000K

Light Source: COB LED

Lumen Output: Warm White 3000K - 650lm/m

Neutral White 4000K - 669lm/m

White 5000K - 688lm/m

CRI: ≥90 Number of LED Per Metre: 560 Wattage Per Metre: 10W 24V DC Input Voltage: 180° Beam angle: Parallel Wiring: **IP67** IP Rating: 25mmCutting Increments/Sections:

Requires: 24V DC Constant Voltage LED Driver


Dimmable: Yes\*\*
IES files: Yes
Continuous Run: 13m Max

\* With the use of Domus drivers

\* All LED strip must be installed on an aluminium heat sink, failure to do so WILL VOID WARRANTY.

\*\* Fully dimmable with suitable dimmers.

### Diagrams / Additional



Item No.	$V_{ariant}$	CCT
PLEX-ULTRA-IP67	24184	3000K
	24185	4000K
	24186	5000K