

MAGNETO-3

















LED Inground Light

Description

Introducing a revolutionary new design in inground lighting. The MAGNETO series from Domus features induction technology to transfer electrical current from the base pot to the light unit WITHOUT any cable connection. This avoids water syphoning through the cables and causing the LED light to prematurely fail due to moisture. Also provides for a very easy maintenance by simply unscrewing the light unit and replacing it without the need for an electrician. Ideal as a path light or inground light close to walls or columns to achieve wall washing or v-line effects. 3W 24V DC LED Inground light, 316 Stainless Steel Light Unit, optic lens diffuser. Available as a spot or flood. 24V DC Constant Voltage LED Driver required.



Input Voltage: 24V DC**
Power (W): 3W
IP rating (IP): IP67

IK Rating (IK) IK10 (2000Kg Drive Over Max) Lumens (Im): Warm White 3000K - 95Im

White 5000K - 95lm

CCT: 3000K - 5000K

CRI: ≥80


Beam angle (°): 25° and 60°

Dimmable: No
Lifespan (hrs): 40,000hrs
Cutout (Ø): Ø60-65mm
Impact rating: IK10
Drive over: 2000Kg





Diagrams / Additional



Cutout: Ø60-65mm

Item No.	Variant	Colour
MAGNETO-3-25D	21080	3000K
	21081	5000K
MAGNETO-3-60D	21082	3000K
	21083	5000K
	21083	5000K

^{**}Requires 24V DC Constant Voltage LED Driver - Wire in Parallel