













# Airsway

## 6 in 1 Premium Bathroom Heater

### Description

The AIRSWAY 6-In-1 Premium Bathroom Heater offers a unique oscillating sway design, as well as the latest technology in PTC bathroom heater models. Premium range offers 6-In-1 Functions — Heater, Exhaust Fan, Circulating Fan, Dry Heat, Sway and Light Unit. Patented Heat Breeze Technology heats the room while offering low level extraction to help reduce condensation build up in the bathroom. This premium line model features a single AC Motor, producing a 2150W output of powerful heat breeze, high volume extraction at 500m³/h, circulating fan to reduce warm temperature build up, and a 25W LED Tri-Colour switchable light. Mode colour indicator offers the consumer an attractive visual coloured indication to which mode is in operation. Digital temperature is displayed discreetly for viewing ambient temperature while in use. Complete with Digital Wall Controller, allowing easy switching from all modes, and an ALL-OFF button for exiting. Domus PTC Bathroom Heaters feature an advanced safety feature where the unit will automatically shut off after two hours in case it is left on accidentally. If the unit runs for two hours continuously, a safety function will automatically turn it off. This setting can be overridden and reset by pressing any switch on the controller within this two-hour period. Ideal for new installations with a slimline 615x315mm fascia frame, and a 595x280mm cutout. Accessories include Digital Controller Wall Control, 3M Flexible Duct, and Exterior Grille. All Domus PTC Bathroom Heaters are backed by our 5 Year In-Home Warranty.

### Specification Features

Input Voltage: 240 V AC
Power (W): 2250 W
Motor Wattage (W): 60 W AC
Fan Size: 60 W
Air Extraction: 500 m³/h
Heat Wattage: 2150 W

Heat Type: PTC Heating Element

 $\begin{array}{ll} \text{Light Wattage:} & 25\text{W LED} \\ \text{IP Rating (IP):} & \text{IPX2} \\ \text{Decibel Rating (dB):} & \leq 48\text{dB} \end{array}$ 

CCT: 3000K - 4000K - 5000K (Changeable)

 Lumen Output
 3000K
 4000K
 5000K

 1900lm
 2150lm
 2100lm


CRI: ≥80


Cutout: 595x280mm
Fascia Size: 615x315mm
Duct Size: 150mm
Product Weight: 7.9Kg

Accessories: 8-Switch Digital Wall Controller, 3M Flexible Duct, Exterior Grille

# multi cc, Trio Technology

### Diagrams / Additional





163mm Height - Minimum 200mm height clearance required



White Wall Controller (Included)



Horizontal Switchplate Film Cover (Included)



Coloured Vertical Switchplate Film Covers (Sold Separately)