DOMUS®

Date: July 2, 2025 10:32 am

Pico-3-Tilt

LED Recessed Downlight

Description

The PICO Series is a miniature downlight range that offers a great solution for cabinet lighting, and display lighting, or for applications where a wall wash effect is required. Available in a 3W fixed or tilt frame, as well as a 7W deep set frame, in the choice of a Black or Satin White powder coated finish. The 24° optical lens diffuser is perfectly matched with the COB high performing LED chipset. Suitable for displays, cabinet lighting, and wall washing, or almost any application where discreet highlighting is required. Complete with a micro sized LED driver and flex and plug.

Now with TRIO, the added option of changing the colour temperature output of the downlight with a dip switch at the back of the fitting. Backed by our Three Year Replacement Warranty.

Specification Features

Input Voltage:	240V AC
Power (W):	3W
IP Rating (IP):	40
Lumens (lm):	Warm White 3000K - 180lm Neutral White 4000K - 210lm White 5700K - 210lm
LED type:	COB
CCT:	3000K - 4000K - 5700K (Switchable)
CRI:	≥90
Beam angle (°):	24°
Dimmable:	Yes*
Lifespan (hrs):	50,000hrs
Cutout (Ø):	Ø45mm

**Fully dimmable with suitable dimmers.*
Black model is 10% lower in lumen output compared to the white model.





Diagrams / Additional





Cutout: Ø45mm - Tilt: 20°
Driver fits through cutout hole

Item No.	Variant		CCT
	Wht	*Blk*	
PICO-3-TILT	21578	21577	TRIO
	DALI		
	21663	21664	TRIO

Please note - DALI Driver may not fit into cutout hole, and may need to be installed by other means.

Domus 29-31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | email: enquiries@domuslighting.com.au
Specification subject to change without prior notice.